

ARRI X2



Cat. No.	Description
502400	ARRI X2
502201	25 ft. Head/Ballast Cable
502202	50 ft. Head/Ballast Cable
502410	Four Leaf Barndoor
502421	Frosted Glass Diffuser
502424	Black Reflector
502245	200W Single Ended HMI Lamp
502806	125/200W Electronic Ballast
502808	125/200W DC Electronic Ballast
502490	Lamphead Case

Photometric Data

Distance	5 ft. (1.5 m)	10 ft. (3.0 m)	15 ft. (4.6 m)	20 ft. (6.1 m)
Beam (120°)				
Footcandles	126	32	14	8
Beam Diameter	17.3 ft. (5.3 m)	34.6 ft. (10.5 m)	52.0 ft. (15.8 m)	69.3 ft. (21.1 m)

Performance at any distance:

$$\text{Footcandles (or lux)} = 3,200 \div \text{Distance}^2 \quad \text{Beam Diameter} = \text{Distance} \times 3.47$$

Specifications

Weight	7 lbs. (3.2 kg)
Reflector	High purity aluminum
Lampholder	GZX 9.5 High Voltage
Mounting	5/8" (16 mm) stand mount
Safety Glass	Clear safety glass

For Ballast Specifications see Ballast Section

