



ARRI X Ceramic 250 (includes lamp and frosted glass)

- 539400 ARRI X Ceramic 250, stand model
- 539401 ARRI X Ceramic 250, hanging model
- 539402 ARRI X Ceramic 250, stand model, black
- 239403 ARRI X Ceramic 250, hanging model, black
- 539420 Filter Frame
- 505410 Barndoor
- 539421 Clear Safety Glass
- 539422 Egg Crate, Black
- 539423 Egg Crate, White
- 539425 Intensifier
- 539426 Chimera 1/4 Diffusion Screen
- 539427 Chimera 50° Soft Eggcrate
- 539430 Snoot
- 539440 250W Ceramic Lamp (spare)

Specifications

Weight: 18lbs. (8.2kg)
 Lampholder: GZY 9.5
 Mounting: 5/8" (16mm) stand mount or hanging model w/c-clamp
 Input Voltage Range: 90-265V 50/60Hz

ARRI Ceramic fixtures feature an integrated igniter/ballast.

ARRI X Ceramic 250 with frosted glass

Measurement distance: 10 ft / 3 m					
Accessories		Intensifier	Intensifier, 1/2 diffusion	Intensifier, 1/4 diffusion	Intensifier, 1/4 diffusion, 50° fabric grid
Illuminance [fc / lux]	45 fc / 485 lx	168 fc / 1795 lx	41 fc / 440 lx	67 fc / 715 lx	58 fc / 625 lx
Beam angle [°]	112°	47°	69°	60°	41°

ARRI X Ceramic 250 with optional clear glass



Measurement distance: 10 ft / 3 m				
Accessories		Intensifier, 1/2 diffusion	Intensifier, 1/4 diffusion	Intensifier, 1/4 diffusion, 50° fabric grid
Illuminance [fc / lux]	42 fc / 450 lx	50 fc / 531 lx	79 fc / 850 lx	72 fc / 772 lx
Beam angle [°]	122°	66°	59°	40°