

ARRI STUDIO Ceramic 250 (includes lamp)

- 539500 Studio Ceramic 250, stand model, 7" lens
- 539501 Studio Ceramic 250, hanging model
- 539502 Studio Ceramic 250, stand model, black
- 539503 Studio Ceramic 250, hanging model
- 531210 Four Leaf Barndoor
- 531215 Eight Leaf Barndoor
- 531220 Filter Frame
- 531230 Snoot
- 531250 9" Full Single Scrim
- 531251 9" Half Single Scrim
- 531252 9" Full Double Scrim
- 531253 9" Half Double Scrim
- 571714 Scrim Bag
- 539440 250W Ceramic Lamp (spare)
- 853276 Safety Cable



Specifications

Weight: 18.5lbs. (8.4kg)

Lampholder : GZY 9.5

Mounting: 5/8" (16mm) stand mount or hanging model w/c-clamp

Input Voltage Range: 90-265V 50/60Hz

ARRI Ceramic fixtures feature an integrated igniter/ballast.

PHOTOMETRIC DATA

DISTANCE	5 ft. (1.5m)	10 ft. (3.0m)	15 ft. (4.6m)	20 ft. (6.1m)
----------	-----------------	------------------	------------------	------------------

Spot Focus beam angle 10°

Footcandles	2699	675	300	169
Beam Diameter	.9 ft. (0.27m)	1.8 ft. (0.55m)	2.6 ft. (0.8m)	3.5 ft. (1.1m)

Flood Focus beam angle 57°

Footcandles	388	97	43	25
Beam Diameter	5.5 ft. (1.7m)	10.9 ft. (3.3m)	16.3 ft. (5.0m)	21.7 ft. (6.6m)

Spot Performance at any distance:

Footcandles (or lux) = 67,500 ÷ Distance² | Beam Diameter = Distance x 0.18

Flood Performance at any distance:

Footcandles (or lux) = 9,700 ÷ Distance² | Beam Diameter = Distance x 1.00