

MINI-FLOOD



Cat. No. Description

572100	MINI-FLOOD
853276	Safety Cable

MINI-FLOOD includes integral barndoor with filter clips

Lamps

Code	FCM	EME	EJG	FCM/HIR	DFD
Watts	1000	800	750	650	500
Volts	120	230	120	120	120
Color Temp (K)	3200	3200	3200	3200	3200
Approx. Life (hrs)	400	250	400	400	400

Photometric Data with FCM 1000W Lamp

Distance	5 ft. (1.5 m)	10 ft. (3.0 m)	15 ft. (4.6 m)	20 ft. (6.0m)
Horizontal Beam Angle 88°				
Vertical Beam Angle 69°				
Footcandles	488	122	54	31
Horizontal Beam Spread	9.5 ft. (2.9 m)	19.0 ft. (5.8 m)	28.5 ft. (8.7 m)	38.0 ft. (11.6 m)

Performance at any distance:

Footcandles (or lux) = $12,202 \div \text{Distance}^2$ Horizontal Beam Diameter = $\text{Distance} \times 1.90$

Specifications

Weight	6.5 lbs. (2.9 kg)
Reflector	High purity aluminum
Lampholder	R7S
Cable	25 ft. cable with inline switch
Mounting	5/8" (16 mm) stand mount

